


Образец регистрационной таблички

 <p>SEACO SRL. Bridgetown, Barbados.</p> <p>TANK SERIAL No: <input type="text" value="SEGU"/></p>																	
<p>MANUFACTURED BY: NANTONG TANK CONTAINER Co., LTD. ADDRESS: 3886 JINTONG HIGHWAY, TONGZHOU, JIANGSU, P.R. CHINA DATE OF MANUFACTURE: <input type="text"/> MANUFACTURER'S SERIAL No: <input type="text" value="NT"/></p>																	
<p>TANK DESIGN CODE UN PORTABLE ASME SECT VII DIV 1/EN14025 TANK TYPE UN PORTABLE TANK T11/L48N</p>																	
<p>CAPACITIES / WEIGHTS NOMINAL LIQUID CAPACITY: 25000 Litres TOTAL MEASURED WATER CAPACITY AT 20°C <input type="text"/> Litres <input type="text"/> U.S.gallons</p>																	
<p>TARE WEIGHT: 3680 kg 8113 lb MAXIMUM PAYLOAD WEIGHT: 32320 kg 71252 lb MAXIMUM GROSS WEIGHT: 36000 kg 79365 lb</p>																	
<p>PRESSURES</p> <table border="0"> <tr> <td>TANK MAWP:</td> <td>4 bar</td> <td>58 psi</td> </tr> <tr> <td>TANK TEST PRESSURE:</td> <td>6 bar</td> <td>87 psi</td> </tr> <tr> <td>STEAM TUBE MAWP:</td> <td>4 bar</td> <td>58 psi</td> </tr> <tr> <td>STEAM TUBE TEST PRESSURE:</td> <td>6 bar</td> <td>87 psi</td> </tr> <tr> <td>EXTERNAL DESIGN PRESSURE:</td> <td>0.41 bar</td> <td>6 psi</td> </tr> </table>			TANK MAWP:	4 bar	58 psi	TANK TEST PRESSURE:	6 bar	87 psi	STEAM TUBE MAWP:	4 bar	58 psi	STEAM TUBE TEST PRESSURE:	6 bar	87 psi	EXTERNAL DESIGN PRESSURE:	0.41 bar	6 psi
TANK MAWP:	4 bar	58 psi															
TANK TEST PRESSURE:	6 bar	87 psi															
STEAM TUBE MAWP:	4 bar	58 psi															
STEAM TUBE TEST PRESSURE:	6 bar	87 psi															
EXTERNAL DESIGN PRESSURE:	0.41 bar	6 psi															
<p>TEMPERATURES</p> <table border="0"> <tr> <td>DESIGN TEMPERATURE RANGE:</td> <td>-40° to 130°C</td> <td>-40°F to 266°F</td> </tr> <tr> <td>MAXIMUM PRODUCT TEMPERATURE:</td> <td>130°C</td> <td>266°F</td> </tr> </table>			DESIGN TEMPERATURE RANGE:	-40° to 130°C	-40°F to 266°F	MAXIMUM PRODUCT TEMPERATURE:	130°C	266°F									
DESIGN TEMPERATURE RANGE:	-40° to 130°C	-40°F to 266°F															
MAXIMUM PRODUCT TEMPERATURE:	130°C	266°F															
<p>MATERIALS</p> <table border="0"> <tr> <td>TANK SHELL & HEADS:</td> <td>SANS 50028-7 WNr 1.4402</td> </tr> <tr> <td>STEAM DUCT:</td> <td>ASTM A240 304</td> </tr> <tr> <td>TANK WELDS:</td> <td>AWS ER316L</td> </tr> <tr> <td>EQUIVALENT MINIMUM SHELL THICKNESS IN MILD STEEL:</td> <td>6.00 mm 0.236 inch</td> </tr> </table>			TANK SHELL & HEADS:	SANS 50028-7 WNr 1.4402	STEAM DUCT:	ASTM A240 304	TANK WELDS:	AWS ER316L	EQUIVALENT MINIMUM SHELL THICKNESS IN MILD STEEL:	6.00 mm 0.236 inch							
TANK SHELL & HEADS:	SANS 50028-7 WNr 1.4402																
STEAM DUCT:	ASTM A240 304																
TANK WELDS:	AWS ER316L																
EQUIVALENT MINIMUM SHELL THICKNESS IN MILD STEEL:	6.00 mm 0.236 inch																
<p>CONNECTIONS</p> <table border="0"> <tr> <td>BOTTOM OUTLET:</td> <td>3" BSP.</td> <td>AIRLINE:</td> <td>1.5" BSP.</td> </tr> <tr> <td>TOP OUTLET:</td> <td>DN80</td> <td>STEAM TUBES:</td> <td>0.75" BSP.</td> </tr> </table>			BOTTOM OUTLET:	3" BSP.	AIRLINE:	1.5" BSP.	TOP OUTLET:	DN80	STEAM TUBES:	0.75" BSP.							
BOTTOM OUTLET:	3" BSP.	AIRLINE:	1.5" BSP.														
TOP OUTLET:	DN80	STEAM TUBES:	0.75" BSP.														

<p>US/DOT, UK/DfT, ADR/RID, IMDG, FRA, AARGO, TC IMPACT APPROVED APPROVAL AUTHORITIES: LLOYDS REGISTER EMEA INSPECTING AUTHORITY: LLOYDS REGISTER EMEA LLOYDS US/DOT NO.: IA-8102</p>			
<p><input checked="" type="checkbox"/> GREAT <input checked="" type="checkbox"/> BRITAIN</p> <p>IMDG APPROVAL NO.: <input type="text" value="GB/MD/LR 63040"/> ADR/RID APPROVAL NO.: <input type="text" value="GB/PT/LR 63040"/> UIC APPROVAL RAILWAYS CODE OR 592</p>			
<p>PERIODIC INSPECTION AND TESTING FIRST & SUBSEQUENT TEST DATES: <input type="text"/> / <input type="text"/> / <input type="text"/> P</p> <p>2.5 YEAR INSPECTION DATE: <input type="text"/> / <input type="text"/> / <input type="text"/> <input checked="" type="checkbox"/></p> <p>TEST PRESSURE: <input type="text"/> / <input type="text"/> / <input type="text"/> <input checked="" type="checkbox"/></p> <p>WITNESS MARK: <input type="text"/> / <input type="text"/> / <input type="text"/> <input checked="" type="checkbox"/></p> <p>5 YEAR TEST DATE: <input type="text"/> / <input type="text"/> / <input type="text"/></p> <p>TEST PRESSURE: <input type="text"/> / <input type="text"/> / <input type="text"/></p> <p>WITNESS MARK: <input type="text"/> / <input type="text"/> / <input type="text"/></p>			
<p>CSC SAFETY APPROVAL</p>			
<p>APPROVAL REFERENCE: <input type="text" value="GB-LR 63040 05/13"/> DATE OF MANUFACTURE: <input type="text"/> IDENTIFICATION No: <input type="text" value="SEGU"/> MAXIMUM GROSS WEIGHT: 36000 kg 79365 lb ALLOWABLE STACK WT. FOR 1.8G: 216000 kg 476198 lb RACKING TEST LOAD VALUE: 150 kN 33721 lb 2R LONGITUDINAL INERTIA & 1R LATERAL INERTIA TESTED ACEP-BDA-01</p>			
<p>APPROVED FOR TRANSPORT UNDER CUSTOMS SEAL</p> <p><input type="text" value="GB/C 63040 LR/2013"/></p>			
<p>TYPE <input type="text" value="NT/25/05"/></p>		<p>MANUFACTURER'S No: <input type="text" value="NT"/></p>	